

LEECH / FULL BATTEN TAPERED PULTRUSION SYSTEM (GLASS -EXPOXY RESIN)

Width		mm 10 (in 0,39)						
Thickness inch		in 0,100	in 0,140	in 0,200				
10		EE 10 100 L/F	EE 10 140 L/F	EE 10 200 L/F				
Width		mm 12 (in 0,47)						
Thickness inch		in 0,050	in 0,070	in 0,090				
12		EE 12 50 L/F	EE 12 70 L/F	EE 12 90 L/F				
Width		mm 15 (in 0,59)						
Thickness inch		in 0,140	in 0,160	in 0,180				
15		EE 15 140 L/F	EE 15 160 L/F	EE 15 180 L/F				
Width		mm 19 (in 0,75)						
Thickness inch		in 0,170	in 0,200	in 0,230	in 0,265	in 0,300	in 0,350	in 0,400
19		EE 19 180 L/F	EE 19 200 L/F	EE 19 230 L/F	EE 19 265 L/F	EE 19 300 L/F	EE 19 350 L/F	EE 19 400 L/F
Width		mm 25 (in 0,98)						
Thickness inch		in 0,360	in 0,420	in 0,520				
25		EE 25 360 L/F	EE 25 420 L/F	EE 25 520 L/F				

RECTANGULAR CONSANT SECTION BATTEN WITH PULTRUSION SYSTEM (GLASS -EXPOXY RESIN)

Available in 20m long reels and diameters starting from 2m or cut to size

STECCH E LEECH / FULL RASTRAMATE PULTRUSE (VETRO-RESINA EPOSSIDICA)

Larghezza		mm 10						
Spessore mm		mm 2,55	mm 3,6	mm 5,1				
10		EE 10 100 L/F	EE 10 140 L/F	EE 10 200 L/F				
Larghezza		mm 12						
Spessore mm		mm 1,35	mm 1,8	mm 2,4				
12		EE 12 50 L/F	EE 12 70 L/F	EE 12 90 L/F				
Larghezza		mm 15						
Spessore mm		mm 3,5	mm 4,0	mm 4,55				
15		EE 15 140 L/F	EE 15 160 L/F	EE 15 180 L/F				
Larghezza		mm 19						
Spessore mm		mm 4,5	mm 5,2	mm 5,9	mm 6,9	mm 7,66	mm 8,8	mm 9,6
19		EE 19 180 L/F	EE 19 200 L/F	EE 19 230 L/F	EE 19 265 L/F	EE 19 300 L/F	EE 19 350 L/F	EE 19 400 L/F
Larghezza		mm 25						
Spessore mm		mm 9,2	mm 10,78	mm 13,18				
25		EE 25 360 L/F	EE 25 420 L/F	EE 25 520 L/F				

STECCH E A SEZIONE RETTANGOLARE COSTANTE PULTRUSE ((VETRO-RESINA EPOSSIDICA)

Disponibili in bobine lunghezza 20 mt e diametro a partire da 2 mt o tagliate a misura